

Model		YGY-121000
Input Characteristics	Input Voltage	90-246V AC
	Input Connecting plug	EU,US,UK,AU,CN plug can be
	Frequency	47-63Hz
	Efficiency	90%
	Input Current	250mA
	Surging Current	25A/220VAC MAX
	Power Factor	PF>0.70(60%-100% Load)
Output Characteristics	Output Voltage	12V DC
	Output Current	1000mA
	Output Power	12W
	Ripple and Noise	100mVp-p
	Voltage Error	±1%
	Linear Adj.Rate	≤2%
	Load Regulation Rate	≤5%
	Start, Rise Time	40ms
Protection	Overcurrent Protection	
	Overload Protection	
	Short Circuit Protection	
	Overvoltage Protection	
	Temperature Protection	
Environment	Working Environment	-5°C-50°C
	Store Environment	-10°C-85°C 20% - 90% RH (I
Insulation	Insulation Strength	3KV
	Insulation Resistance	500VDC>500MΩ
Others	Size(MM)	78*31.5*70
	Weight(g)	105 g
Package	Professional Package(CM)	54*39.5*32.5
	Weight/Cartons	23kg
	Neutral Package(MM)	200pcs/Cartons
	OEM Package(color gift box) designed according to your request	
Application	CCTV Surveillance System,Network Surveillance Camera,DVR,Alarm System,LED,Digital and Electronic Pro	
Certificate	UL/CUL, PSE, GS, BS, CE, CB, FCC	
Feature	Full 2 years Warranty	
	below 0.03% failure factor rate	
	Accurate re UL/CUL, PSE, GS, BS, CE, CB, FCC gulated output,low ripple and low interference	
	Passing QC and aging test for each product	